

## Product

### Microserver High Performance



### Features

- Onboard VIA ESP6000 667 Mhz or ESP1K 1 Ghz CPU
- VIA VT8606 Chipset
- AC97 Audio
- Dual RTL8139C 10/100Mbps LAN
- Type I/II CF
- 2 COM, 2 USB 1.1
- Fanless Design

### Specifications

#### System

<b>CPU</b>	ESP6000 667 Mhz or ESP10K 1 Ghz
<b>BIOS</b>	Award 256 KB Flash BIOS
<b>System</b>	VIA TwisterT VT8606/VT82C686B
<b>I/O Chip</b>	VIA VT82C686B
<b>System</b>	One 144-pin SODIMM socket supports
<b>Memory</b>	128 to 512 MB SDRAM
<b>SSD</b>	One Compact Flash Type I/II socket

#### System

<b>Display</b>	VIA TwisterT VT8606 integrated S3 Savage4 2D/3D graphics accelerator with 32 MB display memory AGP 4X VGA interface 1920 x 1440 @ 16 bpp (60Hz)
<b>Audio</b>	AC97 Audio Mic in, Line in, Line Out
<b>Ethernet</b>	Dual Realtek RTL8139C 10/100Base-TX Fast Ethernet controllers
<b>System Indicators</b>	One LED indicator shows power status
<b>HDD</b>	30 to 80 GB 2.5 inch hard disk
<b>Power</b>	+5V @ 3 amp without hard disk, +5V @ 5 amp with hard disk
<b>Operating Temperature</b>	-20~40 C at 0%~90% relative humidity
<b>Dimensions</b>	5.25 x 6.75 x 2.15 inches
<b>Weight</b>	1100 grams – depends on components installed



**WEB:** [www.norhtec.com](http://www.norhtec.com)  
**Office Phone** Thailand +662 962-1546  
**Mobile Phone** +664 099-4882  
**USA FAX and VOICE MAIL**  
 1 (703) 935 – 8686