

Product



Power Server

Features

- Pentium IV Mini-ITX
- Industrial Grade board
- Support 8286GV + ICH5
- 10/100 BaseT or optional Giga LAN
- 6 COMs w/ +5V, +12V power selector
- Audio support for 5.1 channels
- Does not require air conditioning

Specifications

System

CPU Support Socket 478 Intel Pentium4 / Celeron / Celeron D with 533/400Mhz FSB Processors (800Mhz available)

BIOS AWARD BIOS

System Memory Single Channel with one DDR DIMM socket accepts up to 1GB SDRAM

Enhanced IDE Interface Two 40-pin box header support up to 4 EIDE devices, Ultra DMA transfer 33/66/100 mode and BIOS auto-detect

Serial ATA (SATA) interface Support 2 ports 150MHz Serial ATA Device

System

Display Chipset: INTEL 82801ER/EB + INTEL 82562 EX or INTEL 82547GI for Giga LAN (Optional)

Audio AC97 2.2 Audio Mic in, Line in, Line Out

Power Management ACPI Mode

Real Time Clock On Chip RTC with external Li Battery backup

Watch Dog Timer Programable 1 – 255 seconds / minutes

Digital I/O 2 bit input and 2 bit output (TTL level) by pin header

Device One PCI expansion up to 3 PCI slots via riser card.

HDD 80 GB Standard

Power Internal 200 watt DC powered ATX wth external 12Volt adapter

Operating Temperature -0° – 60°C (32° – 140° F)

Operating Humidity 0% - 90% relative humidity, non-condensing

Dimensions TBA

Weight TBA



WEB: www.norhtec.com

Office Phone Thailand +662 962-1546

Mobile Phone +664 099-4882

USA FAX and VOICE MAIL

1 (703) 935 – 8686

Skype In USA (703) 596-0291 country code +1, United States