



## Product

### MicroServer High Performance



### Features

- Onboard VIA ESP6000 667 Mhz or ESP1K 1 Ghz CPU
- VIA VT8606 Chipset
- AC97 Audio
- Dual RTL8139C 10/100Mbps LAN
- Type I/II CF
- 2 COM, 2 USB 1.1
- Fanless Design

### Specifications

|                 |                                    |
|-----------------|------------------------------------|
| <b>CPU</b>      | ESP6000 667 Mhz or ESP10K 1 Ghz    |
| <b>BIOS</b>     | Award 256 KB Flash BIOS            |
| <b>System</b>   | VIA TwisterT<br>VT8606/VT82C686B   |
| <b>I/O Chip</b> | VIA VT82C686B                      |
| <b>System</b>   | One 144-pin SODIMM socket supports |
| <b>Memory</b>   | 128 to 512 MB SDRAM                |
| <b>SSD</b>      | One Compact Flash Type I/II socket |

|                              |   |
|------------------------------|---|
| <b>CPU</b>                   | ESP6000 667 Mhz or ESP10K 1 Ghz   |
| <b>Display</b>               | VIA TwisterT VT8606<br>Integrated S3 Savage4 2D/3D graphics accelerator with 32 MB display memory AGP 4X<br>VGA interface 1920x1440 @ 16 bpp (60Hz) |
| <b>Audio</b>                 | AC97 Audio Mic in, Line in, Line Out  |
| <b>Ethernet</b>              | Dual Realtek RTL8139C<br>10/100Base-TX Fast Ethernet controllers  |
| <b>System Indicators</b>     | One LED indicator shows power status  |
| <b>HDD</b>                   | 30 to 80 GB 2.5 inch hard disk  |
| <b>Power</b>                 | +5V @ 3 amp without hard disk, +5V @ 5 amp with hard disk   |
| <b>Operating Temperature</b> | -20~40 C at 0%~90% relative humidity  |
| <b>Dimensions</b>            | 5.25 x 6.75 x 2.15 inches   |

**Weight** 1100 gms – depends on components installed



**WEB:** <http://www.norhtec.com>  
**Office Phone** Thailand +662 962-1546  
**Mobile Phone** +664 099-4882  
**USA FAX and VOICE MAIL**  
 1 (703) 935 – 8686